

# HANNEY GROOMING VAN ENGINEERING & DESIGN



DAILY

#### **Fill Fresh Water Tank**

Fill the Fresh Tank by connecting the blue fill hose with black fittings to a standard garden hose. There is an overflow drain hose at the top of the tank in case of over-filling.

#### **Empty HairVac**

Loosen the release knob on the wall behind the HairVac and remove the hose from the port on the side. Swing the Vac out and release the latch to empty into a bag or trash can.

### Clean Force Dryer Filters

Pull off any hair built up on the filters at the top and bottom of the Force Dryer and gently pat the filters with your hand to knock off excess or stuck debris.

## **Clean Fluff Dryer Filter**

You can find the Fluff Dryer filter in the intake bowl on the far side of the Fluff Dryer. Pull it out, knock out any dander or debris, and put it back in place before next use.

## **Drain Gray Water Tank**

Connect a dedicated "dirty water" hose to the valve at the bottom of the tank or use the small connector hose provided to drain out the bottom of the van.

Plug Shoreline in to Charge Plug your extension cord into the Shoreline Port on the back of the van and into a three-prong outlet at your power source. Make sure to fill the tank first.

## **Clean HairVac Filter and Interior**

Use a shop vac or similar vacuum system to clear the filter of any leftover hair and spray the interior with Windex. Wipe down with a cloth to clean.

Pull Excess Hair From A/C Filter Clear any hair from the filter on the back of your A/C with the HairVac housekeeping hose and wand. Don't remove the filter unless absolutely necessary.

#### **Battery Connection Test**

With the van off and unplugged, turn both dryers on and set a timer for 20 minutes. Once the timer goes off, touch each battery connection to see if any are hot and tighten them as needed.

## DEF Top Off

While you wait for the 20 minute timer to go off during battery maintenance, take the time to top off your van's DEF level. This will prevent issues down the road. Battery Water Level Test Check the battery cap gauges to see where the water level is on each battery

where the water level is on each battery cell. If the red bobber is too low, use the siphon pump provided to add distilled water to the appropriate level.

Additional Maintenance For yearly maintenance, cleaning tips, engine upkeep, and more go to GoHanvey.com and click MAINTENANCE in the category menu.

111 KAYAKER WAY EASLEY SC 29642 1-864-269-2912 HANVEYENGINEERING.COM





